





# INSTALLATION RECOMMENDATIONS NO SCALE



**M.D. Hubbard Spring Company**

Engineers and Manufacturers Since 1905  
<https://www.hubbardspring.com> OXFORD, MI - USA



DIAMETER MEASUREMENT:  
 Average of four equally spaced measurements

ROUNDNESS MEASUREMENT:  
 Maximum in diameter measurement must be less than .003

|               |                                          |             |             |                 |                                                        |           |               |                                                                                        |
|---------------|------------------------------------------|-------------|-------------|-----------------|--------------------------------------------------------|-----------|---------------|----------------------------------------------------------------------------------------|
| SCALE:        | 1:1                                      | PROJECTION: |             | MATERIAL TYPE   |                                                        | THICKNESS | PLAIN FINISH  | ELECTRO-PLATED ZINC<br>ASTM B633 SC1 type "V"<br>0.0002" Min.<br>(72 salt spray hours) |
| PRODUCT NAME: | CUP PLUG - ENGLISH<br>SPRING LOCK SERIES |             |             | STEEL           | ASTM A1008/A1008M<br>COLD ROLLED<br>CS TYPE "A" TEMPER | 0.062     | CP-1430-S-62  | CP-1430-S-62-EZ                                                                        |
| PART No.:     | CP-1430                                  | DWG DATE:   | JAN 1, 2026 | STAINLESS STEEL | ASTM A666-304<br>ANNEALED TEMPER                       | 0.062     | CP-1430-KS-62 |                                                                                        |