


+0.008 [0.21]
-0.000
Ø.740 [18.8]




+0.000
-0.005 [0.12]
Ø.362 [9.19]

+0.000
-0.007 [0.18]
Ø.402 [10.2]

0.028 [0.70]

.014 THICK
MAT'L


0.026 [0.66]
FREE HEIGHT
REFERENCE




.012
THICK
MAT'L

.014
THICK
MAT'L

0.748 [19.00]
BEARING
DIAMETER




0.015 [0.38]
LOADED
HEIGHT



.012
THICK
MAT'L

SPRING FORCE
5.55 - 7.50 Lb
24.7 - 33.4 N

0.017 [0.38]
LOADED
HEIGHT



.014
THICK
MAT'L


SPRING FORCE
10.17 - 13.70 Lb
45.2 - 60.9 N

M.D. Hubbard Spring Company

Engineers and Manufacturers Since 1905
<https://www.hubbardspring.com> OXFORD, MI - USA



SCALE: 1:1



PRODUCT NAME: DISC SPRING WASHER - ENGLISH [MM]
LOAD RATED

PART NO.: DSW-740

DWG DATE: JAN 1, 2026

MATERIAL

THICKNESS

FINISH
Vibroground-Light Oil

HIGH CARBON STEEL

ASTM A684/684M - 1074
AUSTEMPERED RC44-47

0.012 [0.30]
0.014 [0.36]

DSW-740-S-12
DSW-740-S-14